

# Grease Trap Guard

Saves Cost on Your Grease Trap Maintenance

Eliminate fat, oil, grease blocks, and keep your grease trap clean, and odorless!



**Mala**TECH  
w a t e r

## Benefits of Grease Trap Guard:

- **Reduces operating cost by decreasing the frequency of pumping** of grease traps significantly
- **High-rate fat, oil, and grease removal** by hydrolysis
- **Eliminates odors in 24 to 48 hours and controls flies**
- Will work in **pH ranges of 4-11**
- Special wetting agents **adhere to the waste in pipes and tanks**
- Begins to **activate existing bacteria** immediately
- **More economical** than treating with conventional chemical and physical treatments
- **Safe, and easy to incorporate into your normal treatment routine**
- **100% all-natural & biodegradable, non-GMO, non-toxic, non-hazardous** product with long shelf life

## Product description:

Grease Trap Guard is a combination of all-natural, high-rate enzyme-producing FOG degrading bacterial strains, specially designed to digest fats, oils and greases using natural ingredients in a natural way. Our scientists have researched environmentally safe and natural systems to lower greases and oils by using them as food source for the microbes. This has a positive effect on the system and allows it to run better, without the use of environmentally hazardous chemicals. Grease Trap Guard is 100% biodegradable, non-toxic and non-hazardous.

Grease Trap Guard also strengthens the existing bacteria that allows it to build up a resistance to harsh conditions.

By having a resistance, the bacteria are constantly feeding and breaking down organic matter while reproducing enzymes that are more effective. This strength allows it to work longer and more efficiently, so the frequency of grease trap pumping drops significantly.

## Fields of application:

- Restaurant grease traps
- Industrial grease traps
- Wastewater treatment plant grease traps
- Wastewater lift stations



## Application of Grease Trap Guarde:

### IMPORTANT INFORMATION

**Recommended dosages are guidelines only. For determining exact dosages for your application, or have any questions, do not hesitate to contact us!**

- 1) Grease trap is recommended to be pumped before initial application
- 2) Initial treatment: 2 litres per thousand-litre tank volume
- 3) Monthly treatment thereafter is 1 litre per thousand-litre tank volume
- 4) Grease Trap Guarde must be poured directly into the grease trap and stirred for about 30 seconds

**Continuous dosage by a low-capacity metering pump is recommended for extremely high FOG load applications.**

### Packaging information:

The product is available in 19 litre safety pails which is the lowest unit for ordering.

### Storage information & shelf life:

Keep the product in a cool and dry place below 28 Celsius. Avoid exposure to direct sunlight. Shelf life is 5 years from manufacturing date.

