

SOS5300 X-15 Super

The Powerful Solution for Concentrated Fat, Oil, Grease or Hydrocarbon Pollution

Supplemental addon for Grease Trap Guarde, and SOS5300 Hydrocarbon Treatment



MalaTECH
water

Benefits of SOS5300 X-15 Super:

- Boosts Grease Trap Guarde application at lift stations & grease traps in eliminating heavy FOG blocks
- Boosts SOS5300 Hydrocarbon Treatment at Hydrocarbon bioremediation when pollution is very concentrated to eliminate Hydrocarbon blocks into small particles for the bacteria to attack
- Replacement for “Caustic” degreasers
- Long shelf life
- Works effectively without introducing environmentally hazardous chemicals
- Safe, and easy to incorporate into your normal treatment routine
- 100% all-natural & biodegradable, non-GMO, non-toxic, non-hazardous product with long shelf life



Product description:

SOS5300 X-15 Super is a microbial product based on all-natural bacteria which secrete powerful enzymes in high amount for breaking down FOG & Hydrocarbons into smaller units. These smaller units then attract the microbes which exist in Grease Trap Guarde & SOS5300 Hydrocarbon Treatment. The microbes use Oxygen to “oxidize” a portion of the carbon, while using the remaining carbon for reproduction of new microbes. The remaining Oxygen is then reduced. This process results in the formation of Carbon dioxide and water. Once the reaction is complete, the process repeats itself until all contaminants are consumed. **SOS5300 X-15 Super is added to Grease Trap Guarde & SOS5300 Hydrocarbon Treatment applications when the FOG & Hydrocarbon pollutions are extremely concentrated.**

Fields of application:

- Biodegradation of Hydrocarbon pollution in contaminated soil (applicable both for in situ, and ex situ applications)
- Biodegradation of Hydrocarbon pollution in contaminated groundwater (applicable both for in situ, and ex situ applications)
- Biodegradation of Hydrocarbon pollution on the surface of freshwater bodies or seawater
- Restaurant grease traps
- Industrial grease traps
- Wastewater treatment plant grease traps
- Wastewater lift stations

Application of SOS5300 X-15 Super:

IMPORTANT INFORMATION

Recommended dosages are guidelines only. For determining exact dosages for your application, or have any questions, do not hesitate to contact us!

Dosage information: 1:1 combination is recommended either with Grease Trap Guarder or with SOS5300 Hydrocarbon Treatment.

Packaging information:

The product is available in 19 litre safety pails which is the lowest unit for ordering.

Storage information & shelf life:

Keep the product in a cool and dry place below 28 Celsius. Avoid exposure to direct sunlight. Shelf life is 5 years from manufacturing date.

